

FORM PTO-1390 (Modified)  
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371

11345.027001

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/674079

INTERNATIONAL APPLICATION NO.  
PCT/IB99/00850

INTERNATIONAL FILING DATE  
29 April 1999 (29.04.99)

PRIORITY DATE CLAIMED  
29 April 1998 (29.04.98)

TITLE OF INVENTION

RECEIVER/DECODER AND METHOD OF PROCESSING VIDEO DATA

APPLICANT(S) FOR DO/EO/US

Jerome MERIC and Patrice LETOURNEUR

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
  - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☒ has been transmitted by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
  - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ have been transmitted by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☒ Certificate of Mailing by Express Mail
20. ☒ Other items or information:



22511

PATENT TRADEMARK OFFICE

Copy of published application WO 99/56465 (26 pages)

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/674079

INTERNATIONAL APPLICATION NO.

PCT/IB99/00850

ATTORNEY'S DOCKET NUMB

11345.027001

21. The following fees are submitted:

CALCULATIONS PTO USE ONLY

**BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5)) :**

- ☐ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... **\$1,000.00**
- ☒ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... **\$860.00**
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... **\$710.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... **\$690.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) ..... **\$100.00**

**ENTER APPROPRIATE BASIC FEE AMOUNT =****\$860.00**

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

**\$0.00**

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	26 - 20 =	6	x \$18.00
Independent claims	5 - 3 =	2	x \$80.00
Multiple Dependent Claims (check if applicable).			<input checked="" type="checkbox"/>

**\$108.00****\$160.00****\$270.00****TOTAL OF ABOVE CALCULATIONS =****\$1,398.00**

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable).

☐**\$0.00****SUBTOTAL =****\$1,398.00**

Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

+

**\$0.00****TOTAL NATIONAL FEE =****\$1,398.00**

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable).

☒**\$40.00****TOTAL FEES ENCLOSED =****\$1,438.00**Amount to be:  
refunded

\$

charged

\$

- ☒ A check in the amount of **\$1,438.00** to cover the above fees is enclosed.
- ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \_\_\_\_\_ to cover the above fees.  
A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **500-591** A duplicate copy of this sheet is enclosed.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

Jonathan P. Osha, Reg. No. 33,986  
ROSENTHAL & OSHA L.L.P.  
700 Louisiana, Suite 4550  
Houston, Texas 77002

Telephone: (713) 228-8600  
Facsimile: (713) 228-8778

SIGNATURE

Jonathan P. Osha

NAME

33,986

REGISTRATION NUMBER

DATE

APPLICATION NO. (IF KNOWN) SHEET OF CFR

09/674079

INTERNATIONAL APPLICATION NO.

PCT/IB99/00850

ATTORNEY'S DOCKET NUMBER

11345.027001

The following fees are submitted:

**NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5)) :**

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO . . . . .

\$1,000.00

- ☒ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO . . . . . \$860.00
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO . . . . . \$710.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) . . . . . \$690.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) . . . . . \$100.00

**ENTER APPROPRIATE BASIC FEE AMOUNT =**

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	26 - 20 =	6	x \$18.00
Independent claims	5 - 3 =	2	x \$80.00

Multiple Dependent Claims (check if applicable). ☒

**TOTAL OF ABOVE CALCULATIONS =**

\$1,398.00

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☐

\$0.00

**SUBTOTAL =**

\$1,398.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

\$0.00

**TOTAL NATIONAL FEE =**

\$1,398.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☒

\$40.00

**TOTAL FEES ENCLOSED =**

\$1,438.00

Amount to be:  
refunded \$  
charged \$

- ☒ A check in the amount of \$1,438.00 to cover the above fees is enclosed.
- ☐ Please charge my Deposit Account No. in the amount of to cover the above fees.
- ☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. 500-591 A duplicate copy of this sheet is enclosed.

**NOTE:** Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Jonathan P. Osha, Reg. No. 33,986  
ROSENTHAL & OSHA L.L.P.  
700 Louisiana, Suite 4550  
Houston, Texas 77002

Telephone: (713) 228-8600  
Facsimile: (713) 228-8778

SIGNATURE

Jonathan P. Osha

NAME

33,986

REGISTRATION NUMBER

DATE

**CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10)**Applicant(s): **Jerome MERIC et al.**

Docket No.

**11345.027001**Serial No.  
**09/ 674079**

Filing Date

Examiner

Group Art Unit

Invention: **RECEIVER/DECODER AND METHOD OF PROCESSING VIDEO DATA**

I hereby certify that the following correspondence:

**PCT U.S. National Phase Application and Attachments; and Preliminary Amendment***(Identify type of correspondence)*

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 in an envelope addressed to: The Assistant Commissioner for Patents, Washington, D.C. 20231 on

10-25-2000*(Date)***Beri Hartwell***(Typed or Printed Name of Person Mailing Correspondence)*  
*(Signature of Person Mailing Correspondence)***EL521607276US***("Express Mail" Mailing Label Number)***Note: Each paper must have its own certificate of mailing.****EL521607276US**

09/674079

PATENT APPLICATION  
ATTORNEY DOCKET NO. 11345.027001

**APPLICATION**  
**FOR**  
**UNITED STATES LETTERS PATENT**

**TITLE:**           **RECEIVER/DECODER AND METHOD OF  
PROCESSING VIDEO DATA**

**APPLICANTS:**   **Jerome MERIC and Patrice LETOURNEUR**

"EXPRESS MAIL" Mailing Label Number: EL521607276US  
Date of Deposit: October 25, 2000



22511

PATENT TRADEMARK OFFICE

005307 6 604 2350

09/ 674 079

526 Rec'd PCT/PTO 25 OCT 2000

PATENT  
ATTORNEY DOCKET NO. 11345.027001

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Jerome MERIC et al.

Art Unit:

Serial No.:

Examiner:

Filed:

Title: RECEIVER/DECODER AND METHOD OF PROCESSING VIDEO DATA

Box PCT Patent Application  
Assistant Commissioner for Patents  
Washington, DC 20231



22511

PATENT TRADEMARK OFFICE

**PRELIMINARY AMENDMENT**

Dear Sir:

Before examining the referenced application on the merits, please amend the application as outlined below:

**In the Abstract:**

In line 2, please delete "comprising" and replace with --including--.

In line 4, please delete "comprising" and replace with --including--.

In line 7, please delete "comprising" and replace with --including--.

**In the Claims:**

In claim 5, line 1, please delete "any preceding claim" and replace with -- claim 1--.

In claim 6, line 1, please delete "any preceding claim" and replace with -- claim 1--.

In claim 8, line 1, please delete “any preceding claim” and replace with -- claim 1--.

In claim 14, line 1, please delete “or 13”.

In claim 16, line 1, please delete “any of Claims 11 to 15” and replace with -- claim 11--.

In claim 17, line 1, please delete “any of Claims 11 to 16” and replace with -- claim 11--.

In claim 19, line 1, please delete “any of Claims 11 to 18” and replace with -- claim 11--.

Please cancel claims 20-22.

**REMARKS**


The claims have been amended to remove multiple dependencies and to correct antecedent basis errors. Full examination and favorable action are requested.

Please charge any fees, or make any credits, to Deposit Account No. 500-591,

Reference No. 11345.027001

Date:

10/20/06



Jonathan P. Osha  
Reg. No. 33,986

Rosenthal & Osha L.L.P.  
700 Louisiana Street, Suite 4550  
Houston, TX 77002

Telephone: 713/228-8600  
Facsimile: 713/6228-8778

11345.027001.20001024.01 doc



*6 pres*

-1-

RECEIVER/DECODER AND METHOD OF PROCESSING VIDEO  
DATA

5 The present invention relates to a receiver/decoder and a method of processing video data.

10 The term "receiver/decoder" used herein may connote a receiver for receiving either encoded or non-encoded signals, for example, television and/or radio signals, which may be broadcast or transmitted by some other means. The term may also connote a decoder for decoding received signals. Embodiments of such receiver/decoders may include a decoder integral with the receiver for decoding the received signals, for example, in a "set-top box", such a decoder functioning in combination with a physically separate receiver, or such a decoder including additional functions, such as a web browser, a video recorder, or a television.

15 In a broadcast digital television system, received signals are passed to a receiver/decoder and thence to a television set. As used herein, the term "digital television system" includes for example any satellite, terrestrial, cable and other system. The receiver/decoder decodes a compressed MPEG-type signal into a television signal for the television set. It is controlled by a remote controller handset, through an interface in the receiver/decoder. The receiver/decoder is used to process the incoming bit stream, and includes a variety of application modules which cause the receiver/decoder to perform a variety of control and other functions.

25 Such a receiver/decoder may have a variety of devices coupled to it, such as a card reader for the user to pass an authorization card through to confirm which services the user is authorized to use, a hand-held television receiver control wand, a television display unit, and a second card reader for use with bank cards to allow the user to perform home banking functions. It may also have a variety of ports coupled to it, for example, a modem for access to the Internet and for conducting home

30

-2-

banking transactions.

The receiver/decoder typically includes a buffering arrangement for handling incoming data. The basic principle of buffering in a receiver/decoder is that a memory section in a memory is designated as a buffer. Incoming data from a port is fed into the buffer. The buffer size may be chosen to be large enough to accommodate most or all incoming messages, or the buffer may be operated with two pointers, one for the point where fresh incoming data is written into the buffer and the other for the point where stored data is read from the buffer.

The receiver/decoder normally includes a 4-layer structure for generating the image to be displayed on the television set, the 4 layers being a stills layer, a moving image layer, a graphics layer, and a cursor layer. The graphics layer is preferably utilized for both icons (typically geometric shapes) and titles (usually but not always subtitles). The use of a common layer, the graphics layer, for both icons and titles causes difficulties in maintaining and updating both the icons and the titles satisfactorily, particularly as a title can appear at any position on the screen.

The main aim of the present invention is to provide an improved buffering arrangement in a receiver/decoder to solve this and other problems.

The present invention provides a method of processing video data in a receiver/decoder comprising at least one port for receiving data and memory means comprising a data buffer area for storing incoming data for display, and a graphics buffer area for storing graphics data, said method comprising passing graphics data stored in the graphics buffer area to the data buffer area for combination with display data stored therein.

In a preferred embodiment, the incoming data comprises video text data, such as one or more subtitles, and the graphics data comprises icon data. When a subtitle screen

-3-

has been fully received in the data buffer area, a central processing unit in the receiver/decoder, under the control of a device, passes icon data into the data buffer area, preferably just before the data stored in the data buffer area is combined with other data to provide video data. Hence, the invention affords the advantage that in the event of an overlap between the icon and part of the subtitle, the icon can be laid over that part of the subtitle, but the non-overlapped parts can be concurrently displayed with the icon.

In a preferred embodiment, the data buffer area comprises two data buffer sub-areas, said incoming display data being directed into one of said sub-areas at a time.

The two sub-areas may be interchanged so that further incoming display data is stored in the other sub-area and graphics data stored in the graphics buffer area is passed to the other sub-area. This can enable a subtitle screen to be stored in one sub-area whilst a previously received subtitle screen is being output from another sub-area, thereby avoiding over-writing of the previously received subtitle screen with fresh data.

Preferably, the two sub-areas are interchanged immediately after graphics data stored in the graphics buffer area is passed to one of the data buffer sub-areas.

The graphics buffer area may comprise a plurality of graphics buffer sub-areas in which graphics data can be stored, graphics data being passed to the data buffer area from a selected one of the graphics buffer sub-areas. This can enable, for example, a number of different icons to be generated and stored prior to the reception of any video text data, so that there is no need for icon generating means to generate continuously icon data.

Preferably, the combined graphics and display data is further combined with other received data to provide video data. Thus, whilst further incoming display data is

-4-

being stored in one data buffer sub-area and graphics data stored in the graphics buffer area is being passed to that data buffer sub-area, the combined data of the other data buffer sub-area can be further combined with the other received data, again thereby avoiding over-writing of the previously received subtitle screen with fresh data.

Preferably, graphics data stored in the graphics buffer area is passed into the data buffer area for combination with display data stored therein immediately before the thus combined graphics and display data is combined with said other received data.

The video data may comprise four layers of data, said combined graphics and display data comprising one of said layers. If so, the four layers of data may comprise said combined graphics and display data layer, a stills data layer, a moving image data layer, and a cursor data layer.

The moving image data layer and the display data may comprise at least part of an MPEG datastream.

The present invention also provides a receiver/decoder comprising at least one port for receiving data, memory means comprising a data buffer area for storing incoming data for display and a graphics buffer area for storing graphics data, and means for passing graphics data stored in the graphics buffer area to the data buffer area for combination with display data stored therein.

A preferred embodiment of the receiver/decoder comprises at least one port for receiving data, a memory comprising a data buffer area for storing incoming data for display and a graphics buffer area for storing graphics data, and a processor for passing graphics data stored in the graphics buffer area to the data buffer area for combination with display data stored therein.

-5-

The data buffer area may comprise two data buffer sub-areas, and the receiver/decoder may further comprise means, for example, a microprocessor, for directing incoming data into one of said sub-areas.

- 5 The receiver/decoder may further comprise control means, such as, for example, a device, the directing means being arranged to direct incoming display data to one of the data buffer sub-areas as specified by said control means.

- 10 The receiver/decoder may further comprise means, for example, a device, for interchanging the two sub-areas so that further incoming display data is storable in the other sub-area and graphics data stored in the graphics buffer area is passable to the other sub-area.

- 15 The interchanging means may be adapted to interchange the two data buffer sub-areas immediately after graphics data stored in the graphics buffer area is passed to one of the data buffer sub-areas.

- 20 The graphics buffer area may comprise a plurality of graphics buffer sub-areas in which graphics data is storable, graphics data being passable to the data buffer area from a selected one of the graphics buffer sub-areas.

- The receiver/decoder may further comprise means for combining the combined graphics and display data with other received data to provide video data. IN one preferred embodiment, the combining means is a mixing circuit.

- 25 The passing means may be arranged to pass graphics data stored in the graphics buffer area into the data buffer area for combination with display data stored therein immediately before combining means combines the combined graphics and display data with said other received data.

30

-6-

The receiver/decoder may further comprise buffer control means, such as, for example, a device, the data buffer sub-areas being defined by the buffer control means.

- 5 The present invention also extends to a broadcast and reception system including a receiver/decoder as aforementioned, and means for broadcasting said data. In a preferred embodiment, the system is a digital television system.

10 Various functions of the receiver/decoder may be implemented in hardware, for example in a dedicated integrated circuit; this may provide enhanced speed of operation. Preferably, however, at least some of the functions are implemented in software, preferably implemented by processing means which runs the applications; this can allow greater flexibility, require less components, and allow the receiver/decoder to be updated more readily.

15 Receiver/decoders embodying the invention will now be described, by way of example, with reference to the drawings, in which:

Figure 1 is a schematic diagram of a digital television system;

20 Figure 2 is a schematic diagram of the structure of a receiver/decoder of the system of Figure 1;

25 Figure 3 is a functional block diagram of the layered architecture of the receiver/decoder;

Figure 4 is a schematic diagram of the arrangement of the graphic processor of the receiver/decoder;

30 Figure 5 is a schematic diagram of a RAM memory of the graphic processor; and

-7-

Figure 6 is a schematic diagram illustrating the combination of layers of a video display.

An overview of a digital television system 1 is shown in Figure 1. The invention includes a mostly conventional digital television system 2 that uses the known MPEG-2 compression system to transmit compressed digital signals. In more detail, MPEG-2 compressor 3 in a broadcast centre receives a digital signal stream (typically a stream of video signals). The compressor 3 is connected to a multiplexer and scrambler 4 by linkage 5.

The multiplexer 4 receives a plurality of further input signals, assembles the transport stream and transmits compressed digital signals to a transmitter 6 of the broadcast centre via linkage 7, which can of course take a wide variety of forms including telecommunications links. The transmitter 6 transmits electromagnetic signals via uplink 8 towards a satellite transponder 9, where they are electronically processed and broadcast via notional downlink 10 to earth receiver 12, conventionally in the form of a dish owned or rented by the end user. The signals received by receiver 12 are transmitted to an integrated receiver/decoder 13 owned or rented by the end user and connected to the end user's television set 14. The receiver/decoder 13 decodes the compressed MPEG-2 signal into a television signal for the television set 14.

Other transport channels for transmission of the data are of course possible, such as terrestrial broadcast, cable transmission, combined satellite/cable links, telephone networks etc.

In a multichannel system, the multiplexer 4 handles audio and video information received from a number of parallel sources and interacts with the transmitter 6 to broadcast the information along a corresponding number of channels. In addition to audiovisual information, messages or applications or any other sort of digital data may be introduced in some or all of these channels interlaced with the transmitted

-8-

digital audio and video information.

A conditional access system 15 is connected to the multiplexer 4 and the receiver/decoder 13, and is located partly in the broadcast centre and partly in the decoder. It enables the end user to access digital television broadcasts from one or more broadcast suppliers. A smartcard, capable of deciphering messages relating to commercial offers (that is, one or several television programmes sold by the broadcast supplier), can be inserted into the receiver/decoder 13. Using the decoder 13 and smartcard, the end user may purchase commercial offers in either a subscription mode or a pay-per-view mode.

As mentioned above, programmes transmitted by the system are scrambled at the multiplexer 4, the conditions and encryption keys applied to a given transmission being determined by the access control system 15. Transmission of scrambled data in this way is well known in the field of pay TV systems. Typically, scrambled data is transmitted together with a control word for descrambling of the data, the control word itself being encrypted by a so-called exploitation key and transmitted in encrypted form.

The scrambled data and encrypted control word are then received by the decoder 13 having access to an equivalent to the exploitation key stored on a smart card inserted in the decoder to decrypt the encrypted control word and thereafter descramble the transmitted data. A paid-up subscriber will receive, for example, in a broadcast monthly ECM (Entitlement Control Message) the exploitation key necessary to decrypt the encrypted control word so as to permit viewing of the transmission.

An interactive system 16, also connected to the multiplexer 4 and the receiver/decoder 13 and again located partly in the broadcast centre and partly in the decoder, enables the end user to interact with various applications via a modern back channel 17. The modem back channel may also be used for communications used in



-9-

the conditional access system 15. An interactive system may be used, for example, to enable the viewer to communicate immediately with the transmission centre to demand authorisation to watch a particular event, download an application etc.

- 5 Referring to Figure 2, the elements of the receiver/decoder 13 or set-top box will now be described. The elements shown in this figure will be described in terms of functional blocks.

10 The decoder 13 comprises a central processor 20 including associated memory elements and adapted to receive input data from a serial interface 21, a parallel interface 22, a modem 23 (connected to the modem back channel 17 of Fig. 1), and switch contacts 24 on the front panel of the decoder.

15 The decoder is additionally adapted to receive inputs from an infra-red remote control 25 via a control unit 26 and also possesses two smartcard readers 27, 28 adapted to read bank or subscription smartcards 29, 30 respectively. The subscription smartcard reader 28 engages with an inserted subscription card 30 and with a conditional access unit 29 to supply the necessary control word to a demultiplexer/descrambler 30 to enable the encrypted broadcast signal to be descrambled. The decoder also includes  
20 a conventional tuner 31 and demodulator 32 to receive and demodulate the satellite transmission before being filtered and demultiplexed by the unit 30.

Processing of data within the decoder is generally handled by the central processor 20. Figure 3 illustrates the software architecture of the central processor 20 of the  
25 receiver/decoder. With reference to Figure 3, the software architecture comprises a Run-Time-Engine 4008, a Device Manager 4068 and a plurality of Devices 4062 and Device Drivers 4066 for running one or more applications 4056.

30 As used in this description, an application is a piece of computer code for controlling high level functions of preferably the receiver/decoder 13. For example, when the

-10-

end user positions the focus of remote control 25 on a button object seen on the screen of the television set 14 and presses a validation key, the instruction sequence associated with the button is run.

5 An interactive application proposes menus and executes commands at the request of the end user and provides data related to the purpose of the application. Applications may be either resident applications, that is, stored in the ROM (or FLASH or other non-volatile memory) of the receiver/decoder 13, or broadcast and downloaded into the RAM or FLASH memory of the receiver/decoder 13.

10 Applications are stored in memory locations in the receiver/decoder 13 and represented as resource files. The resource files comprise graphic object description unit files, variables block unit files, instruction sequence files, application files and data files, as described in more detail in the above-mentioned patent specifications.

15 The receiver/decoder contains memory divided into a RAM volume, a FLASH volume and a ROM volume, but this physical organization is distinct from the logical organization. The memory may further be divided into memory volumes associated with the various interfaces. From one point of view, the memory can be regarded as part of the hardware; from another point of view, the memory can be regarded as supporting or containing the whole of the system shown apart from the hardware.

20 The central processor 20 can be regarded as centred on a run time engine 4008 forming part of a virtual machine 4007. This is coupled to applications on one side (the "high level" side), and, on the other side (the "low level" side), via various intermediate logical units discussed below, to the receiver/decoder hardware 4061, comprising the various ports as discussed above (that is, for example, the serial interface 21, the parallel interface 22, modem 23, and control unit 26).

30 With specific reference to Figure 3, various applications 4057 are coupled to the

-11-

virtual machine 4007; some of the more commonly used applications may be more or less permanently resident in the system, as indicated at 4057, while others will be downloaded into the system, eg from the MPEG data stream or from other ports as required.

5

The virtual machine 4007 includes, in addition to the run time engine 4008, some resident library functions 4006 which include a toolbox 4058. The library contains miscellaneous functions in C language used by the engine 4008. These include data manipulation such as compression, expansion or comparison of data structures, line drawing, etc. The library 4006 also includes information about firmware in the receiver/decoder 13, such as hardware and software version numbers and available RAM space, and a function used when downloading a new device 4062. Functions can be downloaded into the library, being stored in FLASH or RAM memory.

10

15 The run time engine 4008 is coupled to a device manager 4068 which is coupled to a set of devices 4062 which are coupled to device drivers 4060 which are in turn coupled to the ports or interfaces. In broad terms, a device driver can be regarded as defining a logical interface, so that two different device drivers may be coupled to a common physical port. A device will normally be coupled to more than one device driver; if a device is coupled to a single device driver, the device will normally be designed to incorporate the full functionality required for communication, so that the need for a separate device driver is obviated. Certain devices may communicate among themselves.

20

25 As will be described below, there are 3 forms of communication from the devices 4064 up to the run time engine: by means of variables, buffers, and events which are passed to a set of event queues.

25

Each function of the receiver/decoder 13 is represented as a device 4062 in the software architecture of the receiver/decoder 13. Devices can be either local or

30

-12-

remote. Local devices 4064 include smartcards, SCART connector signals, modems, serial and parallel interfaces, a MPEG video and audio player and an MPEG section and table extractor. Remote devices 4066, executed in a remote location, differ from local devices in that a port and procedure must be defined by the system authority or designer, rather than by a device and device driver provided and designed by the receiver/decoder manufacturer.

The run time engine 4008 runs under the control of a microprocessor and a common application programming interface. They are installed in every receiver/decoder so that all receiver/decoders 13 are identical from the application point of view.

The engine 4008 runs applications 4056 on the receiver/decoder 13. It executes interactive applications 4056 and receives events from outside the receiver/decoder 13, displays graphics and text, calls devices for services and uses functions of the library 4006 connected to the engine 4008 for specific computation.

The run time engine 4008 is an executable code installed in each receiver/decoder 13, and includes an interpreter for interpreting and running applications. The engine 4008 is adaptable to any operating system, including a single task operating system (such as MS-DOS). The engine 4008 is based on process sequencer units (which take various events such as a key press, to carry out various actions), and contains its own scheduler to manage event queues from the different hardware interfaces. It also handles the display of graphics and text. A process sequencer unit comprises a set of action-groups. Each event causes the process sequencer unit to move from its current action-group to another action-group in dependence on the character of the event, and to execute the actions of the new action-group.

The engine 4008 comprises a code loader to load and download applications 4056 into the receiver/decoder memory. Only the necessary code is loaded into the RAM or FLASH memory, in order to ensure optimal use. The downloaded data is verified

-13-

by an authentication mechanism to prevent any modification of an application 4056 or the execution of any unauthorized application. The engine 4008 further comprises a decompressor. As the application code (a form of intermediate code) is compressed for space saving and fast downloading from the MPEG stream or via a built-in receiver/decoder mode, the code must be decompressed before loading it into the RAM. The engine 4008 also comprises an interpreter to interpret the application code to update various variable values and determine status changes, and an error checker.

- 10 Before using the services of any device 4062, a program (such as an application instruction sequence) has to be declared as a "client", that is, a logical access-way to the device 4062 or the device manager 4068. The manager gives the client a client number which is referred to in all accesses to the device. A device 4062 can have several clients, the number of clients for each device 4062 being specified depending on the type of device 4062. A client is introduced to the device 4062 by a procedure "Device: Open Channel". This procedure assigns a client number to the client. A client can be taken out of the device manager 4068 client list by a procedure "Device: Close Channel".
- 20 The access to devices 4062 provided by the device manager 4068 can be either synchronous or asynchronous. For synchronous access, a procedure "Device: Call" is used. This is a means of accessing data which is immediately available or a functionality which does not involve waiting for the desired response. For asynchronous access, a procedure "Device: I/O" is used. This is a means of
- 25 accessing data which involves waiting for a response, for example scanning tuner frequencies to find a multiplex or getting back a table from the MPEG stream. When the requested result is available, an event is put in the queue of the engine to signal its arrival. A further procedure "Device: Event" provides a means of managing unexpected events.

-14-

As noted above, the main loop of the run time engine is coupled to a variety of process sequencer units, and when the main loop encounters an appropriate event, control is temporarily transferred to one of the process sequencer units.

5 Thus, it can be seen that the central processor 20 provides a platform having considerable flexibility in enabling an application to communicate with a variety of devices.

10 In the case of received audio and video signals, the MPEG packets containing these signals will be demultiplexed and filtered so as to pass real time audio and video data in the form of a packetised elementary stream (PES) of audio and visual data to dedicated audio and video processors or decoders 33, 34. The converted output from the audio processor 33 passes to a preamplifier 35 and thereafter via the audio output of the receiver/decoder. The converted output from the video processor 34 passes  
15 via a graphic processor 36 and PAL/SECAM encoder 37 to the video output of the receiver/decoder.

20 With reference to Figure 2, the graphic processor 36 is preferably designed to generate a screen display combining moving images together with overlaid text or other images. More specifically it can combine 4 layers; a stills layer, a moving image layer, a graphics layer, and a cursor layer. As described in more detail below, the graphic processor 36 additionally receives graphic data for display (such as generated images etc) from the central processor 20 and combines this information with information received from the video processor 34 to generate the screen display.

25

As shown in more detail in Figure 4, the graphic processor 36 includes dedicated RAM memory area 40, dedicated microprocessor 41 and graphics library 42. With reference to Figure 5, the RAM memory area 40 of the graphic processor 36 is divided into a number of buffer areas; a stills layer buffer area 43, a moving image  
30 layer buffer area 44 and a graphics layer buffer area 45.

-15-

The stills layer is used for background images of a broadly static nature. The circuitry and software associated with the stills layer buffer area 43 can preferably generate an image therein by any desired combination of the following processes:

- generating and filling rectangles with specific colours (defined by up to 24 bits);
- copying images received from the MPEG data stream;
- repeating an image occupying less than the full screen area, to produce a wallpaper effect.

10 The moving image layer is used for the incoming video signals obtained from the MPEG data stream. The circuitry and software associated with the moving image layer buffer area 44 can preferably resize and scale the incoming images, and combine images from a plurality of sources into different areas of the buffer area.

15 The graphics layer is used to produce titles and icons (graphics). Titles are frequently subtitles, which appear centred near the lower edge of the image, but may also appear in other positions on the image. Icons are generally geometric shapes such as rectangles, circles, buttons, and dialogue boxes (it will be realized that the term "icon" is here being used in a broad sense).

20 The graphics layer is defined by one or more rectangular regions, each rectangular region being defined by the coordinates of the upper left corner of the region and the size of the region. Accordingly, the graphics layer buffer area 45 is sub-divided into a plurality of buffer regions 45A, 45B, ... 45N, one buffer region for each of the rectangular regions of the graphics layer. Each buffer region 45A... comprises a plurality of sub-areas 45A<sup>0</sup>, 45A<sup>1</sup>...45A<sup>n</sup>. Each buffer region is created by a "subtitle" device 4062, under the control of an application 4056, in the central processor 20 using a command procedure stored in the graphics library 42.

30 With reference to Figure 6, the contents of the stills layer buffer area 43 and the

-16-

moving image layer buffer area 44, as they are read out, are mixed together by a mixing circuit 50 which can be set to blend (alpha blending, that is, translucently) those outputs; and the output of that mixing circuit 50 is combined with the contents of the graphics layer buffer area 45, as those contents are read out, by a similar mixing circuit 51.

The output of that mixing circuit is combined with the output of a hardware cursor generator 52 by a combining circuit 53 which superposes a cursor signal on the combination of the first 3 layers. The cursor layer is preferably superposed opaquely, that is, without the option of blending, on the combination of the first 3 layers, so that the combination of the first 3 layers is wholly obscured within the area of the cursor. However, one of the bit values available for the cursor pixels is preferably "transparent", so that the cursor can effectively have "holes" in it through which the underlying combined image from the first 3 layers can be seen.

This 4-layer structure produces potential problems with respect to the third layer, that is, the graphics layer. These problems arise because two separate types of display element, titles and icons, are being generated in the same layer. There is therefore the possibility of conflict between these two types of display element. For example, it will often be desirable to change the titles and the icons at different times (and often it will be desirable for the icons to remain in place for longer than the titles). As noted above, the fact that titles may appear in any position on the display, rather than solely in the standard subtitle position, means that such possibility of conflict is substantial.

To overcome this problem, each buffer region 45A, 45B... includes two buffer sub-areas 45A<sup>0</sup> and 45A<sup>1</sup> which are reserved for use by the subtitle device 4062 to build and display subtitles.

The subtitle device 4062 in the central processor 20 selects which of the two buffer



-17-

sub-areas 45A<sup>0</sup> and 45A<sup>1</sup> is to be used to receive incoming data for display and outputs an appropriate command to the graphic processor 36. In turn, the microprocessor 41 of the graphic processor 36 directs incoming data to the selected buffer sub-area. For this purpose, the two buffer sub-areas 45A<sup>0</sup> and 45A<sup>1</sup> are treated  
5 as a "working buffer" and a "display buffer". The sub-area into which currently incoming data is fed is the working buffer, so its contents will be changing.

The received data (subtitles) is directed into the two buffers sub-areas 45A<sup>0</sup> and 45A<sup>1</sup> alternately. In other words, the subtitle device 4062 reverses the roles of the two  
10 sub-areas each time the working buffer has a new complete subtitle page to display, as the contents of that sub-area are no longer changing, giving a steady image which is acceptable to the viewer so that sub-area can be used as the display buffer. The contents of the display buffer are read out as the graphics layer for combination with the combined stills layer and moving image layer. The interval between the  
15 interchange of the roles of the two sub-areas 45A<sup>0</sup> and 45A<sup>1</sup>, that is, between the interchange of the working and display buffers, is typically 5 to 10 s. At that point, the subtitle device 4062 in the central processor 20 outputs an appropriate command to the graphic processor 36 to interchange the roles of the two sub-areas 45A<sup>0</sup> and 45A<sup>1</sup>, and, in turn, the microprocessor 41 of the graphic processor 36 clears the  
20 contents of the other sub-area and directs incoming data to that sub-area.

Each buffer region 45A, 45B... includes a further buffer area, namely an icon buffer area 45A<sup>i</sup>, 45B<sup>i</sup>...., as shown in Figure 5. Each icon buffer area 45A<sup>i</sup> comprises one or more icon buffer sub-areas, 45A<sup>2</sup>, 45A<sup>3</sup>... up to 45A<sup>15</sup>. Each icon buffer sub-area  
25 contains respective icon image data. The icon image may be generated by software stored in the central processor 20, stored in the RAM area 20A (or FLASH memory area) of the central processor 20 and copied by the central processor 20 into a designated icon buffer sub-area of the RAM area 41 of the graphic processor 36. Once an icon image has been stored in the graphic processor 36, it remains in its  
30 buffer sub-area and can be copied repeatedly to either of the two buffer sub-areas

-18-

45A<sup>0</sup> and 45A<sup>1</sup> whenever required. In this way, a whole series of icon images can be constructed, which can be used in whatever sequences and at whatever times are required.

5 The combination of the two images, the subtitles image in one or other of the buffer sub-areas 45A<sup>0</sup> and 45A<sup>1</sup> and the icon image in the icon buffer area 45A<sup>i</sup>, is achieved by copying the icon image into the working buffer, that is, into whichever of the two sub-areas 45A<sup>0</sup> and 45A<sup>1</sup> is not currently the display buffer. As specified by the controlling application, the subtitle device 4062 outputs an appropriate command to  
10 the graphic processor 36 to copy the contents of a specified icon buffer sub-area to the working buffer just before the working buffer is to become the display buffer, that is, when a complete subtitle page has been stored in the working buffer.

With the above arrangement, the icon image currently being displayed is stored in the  
15 display buffer, the next icon image to be displayed may already be stored in the working buffer, and a fresh icon image may be under construction by the icon generator while the working buffer is receiving subtitles data. This arrangement requires synchronism between the interchanging of the working and adjacent play buffers and the construction of fresh icon images.

20 At any time, the application controlling the subtitle device 4062 may require the currently displayed icon image to be changed without alteration of the displayed subtitle, for example, upon input of a command from the remote control 25. In this case, the subtitle device 4062 outputs a command to the graphic processor 36 to copy  
25 an icon image stored in the icon buffer area immediately into the display buffer over the icon image already stored therein.

In summary, when a subtitle screen has been fully received in the data buffer area,  
30 a central processing unit in the receiver/decoder, under the control of a device, passes

-19-

icon data into the data buffer area, preferably just before the data stored in the data buffer area is combined with other data to provide video data. Hence, in the event of an overlap between the icon and part of the subtitle, the icon can be laid over that part of the subtitle, but the non-overlapped parts can be concurrently displayed with the icon.

The precise details of the implementation of the various functions described above, and their distribution between hardware and software, are a matter of choice for the implementor and will not be described in detail. It is, however, noted that dedicated integrated circuits capable of performing the operations required in the receiver/decoder are commercially available or can be readily designed, and these can be used as the basis for a hardware accelerator, or more preferably modified to produce a dedicated hardware accelerator, to implement various of the operations required, thereby reducing the processing power required to run the software. However, the operations required may be implemented in software if sufficient processing power is available.

The modules and other components have been described in terms of the features and functions provided by each component, together with optional and preferable features. With the information given and specifications provided, actual implementation of these features and the precise details are left to the implementor. As an example, certain modules could be implemented in software, preferably written in the C programming language and preferably compiled to run on the processor used to run the application; however, some components may be run on a separate processor, and some or all components may be implemented by dedicated hardware.

The above modules and components are merely illustrative, and the invention may be implemented in a variety of ways, and, in particular, some components may be combined with others which perform similar functions, or some may be omitted in simplified implementations. Hardware and software implementations of each of the

-20-

functions may be freely mixed, both between components and within a single component.

5 It will be readily understood that the functions performed by the hardware, the computer software, and such like are performed on or using electrical and like signals. Software implementations may be stored in ROM, or may be patched in FLASH.

10 It will be understood that the present invention has been described above purely by way of example, and modifications of detail can be made within the scope of the invention. Each feature disclosed in the description, and (where appropriate) the claims and drawings may be provided independently or in any appropriate combination.

CLAIMS

1. A method of processing video data in a receiver/decoder comprising at least one port for receiving data and memory means comprising a data buffer area for storing incoming data for display, and a graphics buffer area for storing graphics data, said method comprising passing graphics data stored in the graphics buffer area to the data buffer area for combination with display data stored therein.

2. A method according to Claim 1, wherein the data buffer area comprises two data buffer sub-areas, said incoming display data being directed into one of said sub-areas at a time.

3. A method according to Claim 2, wherein the two sub-areas are interchanged so that further incoming display data is stored in the other sub-area and graphics data stored in the graphics buffer area is passed to the other sub-area.

4. A method according to Claim 3, wherein the two sub-areas are interchanged immediately after graphics data stored in the graphics buffer area is passed to one of the data buffer sub-areas.

5. A method according to any preceding claim, wherein the graphics buffer area comprises a plurality of graphics buffer sub-areas in which graphics data is stored, graphics data being passed to the data buffer area from a selected one of the graphics buffer sub-areas.

6. A method according to any preceding claim, wherein the combined graphics and display data is further combined with other received data to provide video data.

7. A method according to Claim 6, wherein graphics data stored in the graphics buffer area is passed into the data buffer area for combination with display data stored

-22-

therein immediately before the thus combined graphics and display data is combined with said other received data.

8. A method according to any preceding claim, wherein the video data comprises  
5 four layers of data, said combined graphics and display data comprising one of said layers.

9. A method according to Claim 8, wherein the four layers of data comprise said  
10 combined graphics and display data layer, a stills data layer, a moving image data layer, and a cursor data layer.

10. A method according to Claim 9, wherein the moving image data layer and the display data comprise at least part of an MPEG datastream.

11. A receiver/decoder comprising at least one port for receiving data, memory  
15 means comprising a data buffer area for storing incoming data for display and a graphics buffer area for storing graphics data, and means for passing graphics data stored in the graphics buffer area to the data buffer area for combination with display data stored therein.

20 12. A receiver/decoder according to Claim 11, wherein said data buffer area comprises two data buffer sub-areas, and the receiver/decoder further comprises means for directing incoming data into one of said sub-areas.

25 13. A receiver/decoder according to Claim 12, further comprising control means, the directing means being arranged to direct incoming display data to one of the data buffer sub-areas as specified by said control means.

30 14. A receiver/decoder according to Claim 12 or 13, further comprising means for interchanging the two sub-areas so that further incoming display data is storable in

-23-

the other sub-area and graphics data stored in the graphics buffer area is passable to the other sub-area.

15. A receiver/decoder according to Claim 14, wherein the interchanging means is adapted to interchange the two data buffer sub-areas immediately after graphics data stored in the graphics buffer area is passed to one of the data buffer sub-areas.

16. A receiver/decoder according to any of Claims 11 to 15, wherein the graphics buffer area comprises a plurality of graphics buffer sub-areas in which graphics data is storable, graphics data being passable to the data buffer area from a selected one of the graphics buffer sub-areas.

17. A receiver/decoder according to any of Claims 11 to 16, further comprising means for combining the combined graphics and display data with other received data to provide video data.

18. A receiver/decoder according to Claim 17, wherein the passing means is arranged to pass graphics data stored in the graphics buffer area into the data buffer area for combination with display data stored therein immediately before combining means combines the combined graphics and display data with said other received data.

19. A broadcast and reception system including a receiver/decoder according to any of Claims 11 to 18, and means for broadcasting said data.

20. A method of processing video data in a receiver/decoder substantially as herein described with reference to the accompanying drawings.


21. A receiver/decoder substantially as herein described with reference to the accompanying drawings.

-24-

22. A broadcast and reception system substantially as herein described with reference to the accompanying drawings.



Fig.1.






Fig.3.




Fig.4.




Fig.5.

40 RAM





Fig.6.



**Declaration and Power of Attorney for Patent Application****Déclaration et Pouvoirs pour Demande de Brevet****French Language Declaration****22511**

PATENT TRADEMARK OFFICE

En tant que l'inventeur nommé ci-après, je déclare par le présent acte que:

As a below named inventor, I hereby declare that:

Mon domicile, mon adresse postale et ma nationalité sont ceux figurant ci-dessous à côté de mon nom.

My residence, post office address and citizenship are as stated next to my name.

Je crois être le premier inventeur original et unique (si un seul nom est mentionné ci-dessous), ou l'un des premiers co-inventeurs originaux (si plusieurs noms sont mentionnés ci-dessous) de l'objet revendiqué, pour lequel une demande de brevet a été déposée concernant l'invention intitulée

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

RECEIVER/DECODER AND METHOD OF PROCESSING  
VIDEO DATA

et dont la description est fournie ci-joint à moins que la case suivante n'ait été cochée:

the specification of which is attached hereto unless the following box is checked:

☐ a été déposée le \_\_\_\_\_  
sous le numéro de demande des Etats-Unis ou le numéro  
de demande international PCT

\_\_\_\_\_ et modifiée le \_\_\_\_\_  
(le cas échéant).

☐ was filed on \_\_\_\_\_  
as United States Application Number or PCT  
International Application Number \_\_\_\_\_  
and was amended on \_\_\_\_\_  
(if applicable).

Je déclare par le présent acte avoir passé en revue et compris le contenu de la description ci-dessus, revendications comprises, telles que modifiées par toute modification dont il aura été fait référence ci-dessus.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

Je reconnais devoir divulguer toute information pertinente à la brevetabilité, comme défini dans le Titre 37, § 1.56 du Code fédéral des réglementations.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

## French Language Declaration

Je revendique par le présent acte avoir la priorité étrangère, en vertu du Titre 35, § 119(a)-(d) ou § 365(b) du Code des Etats-Unis, sur toute demande étrangère de brevet ou certificat d'inventeur ou, en vertu du Titre 35, § 365(a) du même Code, sur toute demande internationale PCT désignant au moins un pays autre que les Etats-Unis et figurant ci-dessous et, en cochant la case, j'ai aussi indiqué ci-dessous toute demande étrangère de brevet, tout certificat d'inventeur ou toute demande internationale PCT ayant une date de dépôt précédant celle de la demande à propos de laquelle une priorité est revendiquée.

Prior foreign application(s)  
Demande(s) de brevet antérieure(s)

98401075.1 Europe  
(Number) (Country)  
(Numéro) (Pays)

(Number) (Country)  
(Numéro) (Pays)

Je revendique par le présent acte tout bénéfice, en vertu du Titre 35, §119(e) du Code des Etats-Unis, de toute demande de brevet provisoire effectuée aux Etats-Unis et figurant ci-dessous.

(Application No.)  
(N° de demande)

(Filing Date)  
(Date de dépôt)

(Application No.)  
(N° de demande)

(Filing Date)  
(Date de dépôt)

Je revendique par le présent acte tout bénéfice, en vertu du Titre 35, § 120 du Code des Etats-Unis, de toute demande de brevet effectuée aux Etats-Unis, ou en vertu du Titre 35, § 365(c) du même Code, de toute demande internationale PCT désignant les Etats-Unis et figurant ci-dessous et, dans la mesure où l'objet de chacune des revendications de cette demande de brevet n'est pas divulgué dans la demande antérieure américaine ou internationale PCT, en vertu des dispositions du premier paragraphe du Titre 35, § 112 du Code des Etats-Unis, je reconnais devoir divulguer toute information pertinente à la brevetabilité, comme défini dans le Titre 37, § 1.56 du Code fédéral des réglementations, dont j'ai pu disposer entre la date de dépôt de la demande antérieure et la date de dépôt de la demande nationale ou internationale PCT de la présente demande:

PCT/IB99/00850 29 April 1999  
(Application No.) (Filing Date)  
(N° de demande) (Date de dépôt)

(Application No.) (Filing Date)  
(N° de demande) (Date de dépôt)

Je déclare par le présent acte que toute déclaration ci-incluse est, à ma connaissance, véridique et que toute déclaration formulée à partir de renseignements ou de suppositions est tenue pour véridique; et de plus, que toutes ces déclarations ont été formulées en sachant que toute fausse déclaration volontaire ou son équivalent est passible d'une amende ou d'une incarcération, ou des deux, en vertu de la Section 1001 du Titre 18 du Code des Etats-Unis, et que de telles déclarations volontairement fausses risquent de compromettre la validité de la demande de brevet ou du brevet délivré à partir de celle-ci.

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below, and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed  
Droit de priorité revendiqué

29 April 1998  
(Day/Month/Year Filed)  
(Jour/Mois/Année de dépôt)

(Day/Month/Year Filed)  
(Jour/Mois/Année de dépôt)

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

Pending  
(Status) (patented, pending, abandoned)  
(Statu) (breveté, en cours d'examen, abandonné)

(Status) (patented, pending, abandoned)  
(Statu) (breveté, en cours d'examen, abandonné)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.



**French Language Declaration**

POUVOIRS: En tant que l'inventeur cité, je désigne par la présente l'(les) avocat(s) et/ou agent(s) suivant(s) pour qu'ils poursuive(nt) la procédure de cette demande de brevet et traite(nt) toute affaire s'y rapportant avec l'Office des brevets et des marques: (mentionner le nom et le numéro d'enregistrement).

Adresser toute correspondance à:

Adresser tout appel téléphonique à: (nom et numéro de téléphone)



POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: (list name and registration number).

Send Correspondence to:

Jonathan P. Osha  
Rosenthal & Osha L.L.P.  
700 Louisiana, Suite 4550  
Houston, Texas 77002

Direct Telephone Calls to: (name and telephone number)

Jonathan P. Osha (713) 228-8600

Nom complet de l'unique ou premier inventeur		Full name of sole or first inventor	
		<u>Jerome MERIC</u>	
Signature de l'inventeur	Date	Inventor's signature	Date
			<u>16.10.00</u>
Domicile		Residence	
		<u>55, rue de Meaux, F-60300 Senlis, FRANCE</u> <u>FRX</u>	
Nationalité		Citizenship	
		<u>FRANCE</u>	
Adresse postale		Post Office Address	
		<u>55, rue de Meaux, F-60300 Senlis, FRANCE</u>	
Nom complet du second co-inventeur, le cas échéant		Full name of second joint inventor, if any	
		<u>Patrice LETOURNEUR</u>	
Signature du second inventeur	Date	Second Inventor's signature	Date
			<u>16.10.00</u>
Domicile		Residence	
		<u>44, rue Cluseret, F-92150, Suresnes, FRANCE</u> <u>FRX</u>	
Nationalité		Citizenship	
		<u>FRANCE</u>	
Adresse postale		Post Office Address	
		<u>44, rue Cluseret, F-92150, Suresnes, FRANCE</u>	

(Fournir les mêmes renseignements et la signature de tout co-inventeur supplémentaire.) (Supply similar information and signature for third and subsequent joint inventors.)